

September 29, 2015

Mr. Giles Rhoads
City of Riviera Beach
Attn: Utility District Admin Bldg
600 Blue Heron Boulevard West
Riviera Beach, FL 33404-4311

Phone: (561) 845-4185
Email: grhoads@rivierabch.com

**RE: Lift Station Back-Up Pumps
Sale Quotation 145001490**

Dear Mr. Rhoads:

Thank you for your interest in Xylem Dewatering Solutions d/b/a Godwin Pumps of America and the products and services we provide. Attached is the sales quotation requested for emergency back-up pumps of the city's lift station system.

We backed into the pump selection based on the lift station information provided by the city and by them also prioritizing each station by the critical response needed and please see our pump model selection below:

Lift Stations 4,12,20,21,22,25,29,28,29,40,43,44

Based on the flows, suction lift, and discharge heads on these stations we recommend the Godwin Pump CD103M 4" Dri-Prime Pump with Critically Silenced Enclosure. The CD103M has maximum flows up to 1,000 gallons per minute, maximum totally dynamic heads up to 170', maximum suction lift up to 28' and solids handling capabilities of 3". The Critically Silenced Enclosure keep sound levels to approximately 69 dBA at 30 feet and the unit can be removed from the trailer for security purposes. We will utilize the Isuzu 4LE2T Final Tier 4 Diesel Engine to drive the pump with a Prime Guard Control Panel for operating the unit. The Prime Guard Panel will enable to remotely operate the pumps via high/low floats for starting and stopping based on the level of the wet well and there are dry contacts located in the panel to tie into the city's SCADA for default warning such as pump running, not in auto, etc. for even more reliability and assurance.

Lift Stations 18 & 23

Based on the flows, suction lift, and discharge heads on these stations we recommend the Godwin Pump CD150M 6" Dri-Prime Pump with Critically Silenced Enclosure. The CD150M has maximum flows up to 2,080 gallons per minute, maximum totally dynamic heads up to 167', maximum suction lift up to 28' and solids handling capabilities of 3". The Critically Silenced Enclosure keep sound levels to approximately 69 dBA at 30 feet and the unit can be removed from the trailer for security purposes. We will utilize the John Deere 4045T290 Interim Tier 4 Diesel Engine to drive the pump with a Prime Guard Control Panel for operating the unit. The Prime Guard Panel will enable to remotely operate the pumps via high/low floats for starting and stopping based on the level of the wet well and there are dry contacts located in the panel to tie into the city's SCADA for default warning such as pump running, not

in auto, etc. for even more reliability and assurance.

Lift Stations 10 & 41

Based on the flows, suction lift, and discharge heads on these stations we recommend the Godwin CD225M 8" Dri-Prime Pump with Critically Silenced Enclosure. The CD225M has maximum flows up to 3,100 gallons per minute, maximum totally dynamic heads up to 170', maximum suction lift up to 28' and solids handling capabilities of 3-1/8". The Critically Silenced Enclosure keep sound levels to approximately 69 dBA at 30 feet and the unit can be removed from the trailer for security purposes. We will utilize the JCB TCAE-93 Final Tier 4 Diesel Engine to drive the pump with a Prime Guard Control Panel for operating the unit. The Prime Guard Panel will enable to remotely operate the pumps via high/low floats for starting and stopping based on the level of the wet well and there are dry contacts located in the panel to tie into the city's SCADA for default warning such as pump running, not in auto, etc. for even more reliability and assurance.

BASED ON CONVERSATIONS AND BUDGET ALLOWING THE CITY TO PURCHASE (2) PUMPS WE RECOMMEND NOT PURCHASING THE CD225M and utilizing the Godwin CD150M 6" Dri-Prime Pump and Godwin CD103M 4" Dri-Prime Pump together on these stations to cover the flows. YOU CANNOT combine discharge lines if utilizing both pumps; they would need separate discharge piping.

Lift Stations 1A, 47, & 50

These are all high flow stations outside the scope of the Godwin CD103M, CD150M, and CD225M and our recommendation is for a site visit and to implement a rental contingency plan for these.

We did not see flow information for lift stations 2,3,5,7,15, or 35 unless we missed something, but none of those were designated as Critical Stations.

Pricing is all based on the Florida Sheriff's Contract Bid # 15-13-0904 that is valid from 10/01/15 through 09/30/16 and pricing includes freight to your facility.

Keep in mind we also offer suction hose, discharge hose, or other piping needs for the pumps. Also keep in mind the versatility of the pumps and knowing suction lift, discharge head or pressures is key to successfully apply the units on the different stations for optimum performance.

Please call with any questions.

Sincerely,

Thomas Blanford
Outside Sales Representative

TB / gy

SALE QUOTATION

ITEM	QTY	DESCRIPTION	UNIT PRICE	SALE TOTAL
Contract Items:				
A	1	Godwin Dri-Prime CD103M Critically Silenced <ul style="list-style-type: none"> • Sound Attenuated Enclosure • 4" 150# Flanged Suction & Discharge • Isuzu 4LE2T FT4 Diesel Engine • Includes PrimeGuard Engine Controller • Skid-mounted • Engine/Motor Options <ul style="list-style-type: none"> • Battery Charger - 12 Volt Trickle • Base Options <ul style="list-style-type: none"> • Lights - 12 Volt Work Lights <ul style="list-style-type: none"> • (4) Mounted on exterior(each corner) of Critically Silenced enclosure. Includes 15 minute timer. • Lights - Interior <ul style="list-style-type: none"> • One (1) includes 15 minute timer - Mounted over PrimeGuard • Spare Tire 	\$ 47,022.00	\$ 47,022.00
B	1	CD100M/150M SAE GL5 Trailer (5852)	0.00	0.00
C	1	Godwin PrimeGuard Float Set <ul style="list-style-type: none"> • w/ 65' Mechanical Floats 	347.00	347.00
D	1	Godwin Dri-Prime CD150M Critically Silenced <ul style="list-style-type: none"> • Sound Attenuated Enclosure • 6" 150# Flange Suction and Discharge • John Deere 4045T290SP2 IT4 Diesel Engine, Skid-mounted • Engine/Motor Options <ul style="list-style-type: none"> • PrimeGuard Controller • Battery Charger - 12 Volt Trickle • Base Options <ul style="list-style-type: none"> • Lights - 12 Volt Work Lights <ul style="list-style-type: none"> • (4) Mounted on exterior(each corner) of Critically Silenced enclosure. Includes 15 minute timer. • Lights - Interior <ul style="list-style-type: none"> • One (1) includes 15 minute timer - Mounted over PrimeGuard 	43,280.00	43,280.00
			1,332.00	1,332.00
			0.00	0.00
			444.00	444.00
			315.00	315.00

Please note all sale pricing is in U.S. Dollars. The price does not include freight, export boxing, duties, taxes, or any other items not specifically mentioned.

This pricing information is for internal use only. We ask that these items and terms be kept confidential. All applicable tax and freight charges will be added to invoices. All quotations are subject to credit approval. All quotations are valid for 10 days. All prices quoted in US dollars.

SALE QUOTATION

ITEM	QTY	DESCRIPTION	UNIT PRICE	SALE TOTAL
		• Spare Tire	0.00	0.00
E	1	CD150/HS150 Drop In Trailer (9233)	0.00	0.00
F	1	Godwin PrimeGuard Float Set • w/ 65' Mechanical Floats	347.00	347.00
G	1	DELIVERY MOTOR FRT BR 045 PARTIAL LOAD • No Delivery Charges - Per the FSA Contract	TBD	TBD
<div> <p>Due to a limited supply of the interim Tier 4 diesel engines, this quotation is valid for 10 business days from date of issue. Contact our office if an updated quotation is required.</p> </div>				

Please note all sale pricing is in U.S. Dollars. The price does not include freight, export boxing, duties, taxes, or any other items not specifically mentioned.

This pricing information is for internal use only. We ask that these items and terms be kept confidential. All applicable tax and freight charges will be added to invoices. All quotations are subject to credit approval. All quotations are valid for 10 days. All prices quoted in US dollars.