

CITY OF RIVIERA BEACH

BRUSH HAWG

QUOTATION

M2 106 CONVENTIONAL CHASSIS

| | |
|---|---|
| SET BACK AXLE - TRUCK | DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE |
| CUM ISB 6.7-280 280 HP @ 2300 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM | 12,000# MONO TAPERLEAF FRONT SUSPENSION |
| ALLISON 3500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION | 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB |
| RS-23-160 23,000# R-SERIES SINGLE REAR AXLE | 6450MM (254 INCH) WHEELBASE |
| 23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER | 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 1925MM (76 INCH) REAR FRAME OVERHANG |

| | TOTAL # OF UNITS (1) | PER UNIT | TOTAL |
|----------------------------------|----------------------|-----------|-------|
| VEHICLE PRICE | \$ | \$ | |
| EXTENDED WARRANTY | \$ | \$ | |
| DEALER INSTALLED OPTIONS | \$ | \$ | |
| CUSTOMER PRICE BEFORE TAX | \$ | \$ | |

TAXES AND FEES

| | | |
|----------------|----|----|
| TAXES AND FEES | \$ | \$ |
| OTHER CHARGES | \$ | \$ |

TRADE-IN

| | | | | | |
|---------------------------|-------------------------|-----------|----------------|-----------|----------------|
| TRADE-IN ALLOWANCE | \$ | (0) | \$ | (0) | |
| BALANCE DUE | (LOCAL CURRENCY) | \$ | 148,551 | \$ | 148,551 |

2015/16 FLORIDA SHERIFFS CONTRACT SPEC 12 15-13-0904

LOU BACHRODT FREIGHTLINER LOW BID ON THIS SPEC.

APPROVAL:

Please indicate your acceptance of this quotation by signing below:

Customer: X _____ Date: ___ / ___ / ___.



Daimler Truck Financial

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at Information@dtoffers.com.

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at www.daimler-truckfinancial.com.



S P E C I F I C A T I O N P R O P O S A L

Description

Price Level

M2 PRL-10M (EFF:02/11/15)

Data Version

SPECPRO21 DATA RELEASE VER 006

Vehicle Configuration

M2 106 CONVENTIONAL CHASSIS
2016 MODEL YEAR SPECIFIED
SET BACK AXLE - TRUCK
STRAIGHT TRUCK PROVISION
LH PRIMARY STEERING LOCATION

General Service

TRUCK CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND
CARB OPT-IN STATES)
PICKUP AND DELIVERY/SHORT HAUL SERVICE
GOVERNMENT BUSINESS SEGMENT
DRY BULK COMMODITY
TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN
TRANSIT, IS SPENT ON NON-PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
MAINTAINED GRAVEL OR CRUSHED ROCK -
MOST SEVERE IN-TRANSIT (BETWEEN SITES)
ROAD SURFACE
MEDIUM TRUCK WARRANTY
EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD :
23000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 35000.0 lbs

Truck Service

FLATBED/PLATFORM/STAKE BODY



Description

EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE
FRAME "XX" INCHES : 32.0 in

Engine

CUM ISB 6.7-280 280 HP @ 2300 RPM, 2600 GOV,
660 LB/FT @ 1600 RPM

Electronic Parameters

70 MPH ROAD SPEED LIMIT
CRUISE CONTROL SPEED LIMIT SAME AS ROAD
SPEED LIMIT
PTO MODE ENGINE RPM LIMIT - 1100 RPM
PTO MODE BRAKE OVERRIDE - SERVICE
BRAKE APPLIED
PTO RPM WITH CRUISE SET SWITCH - 700 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 800
RPM
PTO MODE CANCEL VEHICLE SPEED - 5 MPH
PTO GOVERNOR RAMP RATE - 250 RPM PER
SECOND
PTO MINIMUM RPM - 700
REGEN INHIBIT SPEED THRESHOLD - 5 MPH

Engine Equipment

2015 ONBOARD DIAGNOSTICS/2010
EPA/CARB/GHG14
NO 2008 CARB EMISSION CERTIFICATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
ONE PIECE VALVE COVER
SIDE OF HOOD AIR INTAKE WITH FIREWALL
MOUNTED DONALDSON AIR CLEANER
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
ALTERNATOR WITH REMOTE BATTERY VOLT
SENSE
(2) ALLIANCE MODEL 1131, GROUP 31, 12 VOLT
MAINTENANCE FREE 1900 CCA THREADED
STUD BATTERIES, NON FCCC ONLY
BATTERY BOX FRAME MOUNTED
STANDARD BATTERY JUMPERS
SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE UNDER CAB
WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
NON-POLISHED BATTERY BOX COVER



Description

CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE
STANDARD MECHANICAL AIR COMPRESSOR
GOVERNOR
AIR COMPRESSOR DISCHARGE LINE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM
RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH HORIZONTAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND DASH MOUNTED REGENERATION
REQUEST SWITCH
STANDARD EXHAUST SYSTEM LENGTH
RH STANDARD HORIZONTAL TAILPIPE
6 GALLON DIESEL EXHAUST FLUID TANK
100 PERCENT DIESEL EXHAUST FLUID FILL
LH MEDIUM DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID PUMP
MOUNTING
STANDARD DIESEL EXHAUST FLUID TANK CAP
HORTON HT650 FRONTAL AIR ON/OFF ENGINE
FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH
SWITCH, NON ENGINE MOUNTED
CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
950 SQUARE INCH ALUMINUM RADIATOR
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-
CHARGED SCA HEAVY DUTY COOLANT
GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
CONSTANT TENSION HOSE CLAMPS FOR
COOLANT HOSES
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
ALUMINUM FLYWHEEL HOUSING
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 29MT STARTER WITH INTEGRATED
MAGNETIC SWITCH

Transmission



Description

ALLISON 3500 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV

ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY

NEUTRAL AT STOP - DISABLED, FUELSense -
DISABLED

VEHICLE INTERFACE WIRING CONNECTOR
WITHOUT BLUNT CUTS, AT BACK OF CAB

ELECTRONIC TRANSMISSION CUSTOMER
ACCESS CONNECTOR MOUNTED BACK OF CAB

CUSTOMER INSTALLED CHELSEA 277 SERIES
PTO

PTO MOUNTING, LH SIDE OF MAIN
TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN

PUSH BUTTON ELECTRONIC SHIFT CONTROL,
DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER, IN
RADIATOR END TANK

TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74
DROP SINGLE FRONT AXLE

MERITOR 15X4 Q+ CAM FRONT BRAKES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

Description

SKF SCOTSEAL PLUS XL FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL
STANDARD SPINDLE NUTS FOR ALL AXLES
MERITOR AUTOMATIC FRONT SLACK
ADJUSTERS
TRW THP-60 POWER STEERING
POWER STEERING PUMP
2 QUART SEE THROUGH POWER STEERING
RESERVOIR
SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

12,000# MONO TAPERLEAF FRONT
SUSPENSION
MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RS-23-160 23,000# R-SERIES SINGLE REAR
AXLE
6.43 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
MXL 17T MERITOR EXTENDED LUBE MAIN
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - SINGLE REAR AXLE
(1) DRIVER CONTROLLED DIFFERENTIAL LOCK
REAR VALVE FOR SINGLE DRIVE AXLE
BLINKING LAMP WITH EACH MODE SWITCH,
DIFFERENTIAL UNLOCK WITH IGNITION OFF,
ACTIVE <5 MPH
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR
BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON FORWARD
SIDE OF DRIVE AXLE(S)
CONMET CAST IRON REAR BRAKE DRUMS
REAR BRAKE DUST SHIELDS
SKF SCOTSEAL PLUS XL REAR OIL SEALS
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE
AXLE SPRING PARKING CHAMBERS

Description

MERITOR AUTOMATIC REAR SLACK
ADJUSTERS
SYNTHETIC 75W-90 REAR AXLE LUBE

Rear Suspension

23,000# 52 INCH VARIABLE RATE MULTI-LEAF
SPRING REAR SUSPENSION WITH LEAF
SPRING HELPER
SPRING SUSPENSION - NO AXLE SPACERS
STANDARD AXLE SEATS IN AXLE CLAMP
GROUP

Brake System

AIR BRAKE PACKAGE
WABCO 4S/4M ABS WITHOUT TRACTION
CONTROL
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
FIBER BRAID PARKING BRAKE HOSE
STANDARD BRAKE SYSTEM VALVES
STANDARD AIR SYSTEM PRESSURE
PROTECTION SYSTEM
STD U.S. FRONT BRAKE VALVE
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER
AIR DRYER MOUNTED UNDER HOOD
STEEL AIR BRAKE RESERVOIRS
CLEAR FRAME RAILS FROM BACK OF CAB TO
FRONT REAR SUSPENSION BRACKET, BOTH
RAILS OUTBOARD
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER
ON ALL TANK(S)

Trailer Connections

UPGRADED CHASSIS MULTIPLEXING UNIT
UPGRADED BULKHEAD MULTIPLEXING UNIT

Wheelbase & Frame

6450MM (254 INCH) WHEELBASE
11/32X3-1/2X10-15/16 INCH STEEL FRAME
(8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
1925MM (76 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 71 INCH TO 80
INCH



Description

CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
188.45 in
CALCULATED EFFECTIVE BACK OF CAB TO
REAR SUSPENSION C/L (CA) : 185.45 in
CALC'D FRAME LENGTH - OVERALL : 359.39
CALC'D SPACE AVAILABLE FOR DECKPLATE :
188.45 in
CALCULATED FRAME SPACE LH SIDE : 211.64
in
CALCULATED FRAME SPACE RH SIDE : 191.96
in
SQUARE END OF FRAME
FRONT CLOSING CROSSMEMBER
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD MIDSHIP #1 CROSSMEMBER(S)
STANDARD REARMOST CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER

Chassis Equipment

THREE-PIECE 14 INCH STEEL CENTER BUMPER
WITH FLEXIBLE PLASTIC ENDS
FRONT TOW HOOKS - FRAME MOUNTED
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
FENDER AND FRONT OF HOOD MOUNTED
FRONT MUDFLAPS
GRADE 8 THREADED HEX HEADED FRAME
FASTENERS

Fuel Tanks

50 GALLON/189 LITER SHORT RECTANGULAR
ALUMINUM FUEL TANK - LH
RECTANGULAR FUEL TANK(S)
PLAIN ALUMINUM/PAINTED STEEL
FUEL/HYDRAULIC TANK(S) WITH PAINTED
BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
FUEL TANK CAP(S)
ALLIANCE FUEL FILTER/WATER SEPARATOR
WITH PRIMER PUMP
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON
FUEL LINE

| Description |
|---|
| Tires |
| HANKOOK AH12 11R22.5 16 PLY RADIAL FRONT TIRES |
| HANKOOK DL11 11R22.5 16 PLY RADIAL REAR TIRES |
| Hubs |
| CONMET PRESET PLUS IRON FRONT HUBS |
| CONMET PRESET PLUS IRON REAR HUBS |
| Wheels |
| 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC FRONT WHEELS |
| 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC REAR WHEELS |
| FRONT WHEEL MOUNTING NUTS |
| REAR WHEEL MOUNTING NUTS |
| Cab Exterior |
| 106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB |
| RUBBER CAB MOUNTS |
| LH AND RH GRAB HANDLES |
| PAINTED PLASTIC GRILLE |
| ARGENT SILVER HOOD MOUNTED AIR INTAKE GRILLE |
| FIBERGLASS HOOD |
| SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK |
| DUAL ELECTRIC HORNS |
| SINGLE HORN SHIELD |
| DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME |
| REAR LICENSE PLATE MOUNT END OF FRAME |
| INTEGRAL HEADLIGHT/MARKER ASSEMBLY |
| (5) AMBER MARKER LIGHTS |
| INTEGRAL STOP/TAIL/BACKUP LIGHTS |
| STANDARD FRONT TURN SIGNAL LAMPS |
| DUAL WEST COAST BRIGHT FINISH MIRRORS |
| DOOR MOUNTED MIRRORS |
| 102 INCH EQUIPMENT WIDTH |



Description

LH AND RH 8 INCH BRIGHT FINISH CONVEX
MIRRORS MOUNTED UNDER PRIMARY
MIRRORS
STANDARD SIDE/REAR REFLECTORS
63X14 INCH TINTED REAR WINDOW
TINTED DOOR GLASS LH AND RH WITH TINTED
NON-OPERATING WING WINDOWS
MANUAL DOOR WINDOW REGULATORS
TINTED WINDSHIELD
2 GALLON WINDSHIELD WASHER RESERVOIR
WITHOUT FLUID LEVEL INDICATOR, FRAME
MOUNTED

Cab Interior

OPAL GRAY VINYL INTERIOR
MOLDED PLASTIC DOOR PANEL
MOLDED PLASTIC DOOR PANEL
BLACK MATS WITH SINGLE INSULATION
FORWARD ROOF MOUNTED CONSOLE WITH
UPPER STORAGE COMPARTMENTS WITHOUT
NETTING
IN DASH STORAGE BIN
(2) CUP HOLDERS LH AND RH DASH
GRAY/CHARCOAL FLAT DASH
HEATER, DEFROSTER AND AIR CONDITIONER
STANDARD HVAC DUCTING
MAIN HVAC CONTROLS WITH RECIRCULATION
SWITCH
STANDARD HEATER PLUMBING
DENSO HEAVY DUTY AIR CONDITIONER
COMPRESSOR
BINARY CONTROL, R-134A
STANDARD INSULATION
SOLID-STATE CIRCUIT PROTECTION AND
FUSES
12V NEGATIVE GROUND ELECTRICAL SYSTEM
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED
BY LH AND RH DOORS
CAB DOOR LATCHES WITH MANUAL DOOR
LOCKS
BASIC HIGH BACK AIR SUSPENSION DRIVER
SEAT WITH MECHANICAL LUMBAR AND
INTEGRATED CUSHION EXTENSION

Description

2 MAN TOOL BOX MID BACK NON SUSPENSION
PASSENGER SEAT
LH AND RH INTEGRAL DOOR PANEL ARMRESTS
VINYL WITH VINYL INSERT DRIVER SEAT
VINYL WITH VINYL INSERT PASSENGER SEAT
3 POINT DRIVER AND PASSENGER AND 2 POINT
CENTER FRONT SEAT BELT RETRACTORS
FIXED STEERING COLUMN
4-SPOKE 18 INCH (450MM) STEERING WHEEL
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL
GRAY CENTER INSTRUMENT PANEL
BLACK GAUGE BEZELS
LOW AIR PRESSURE INDICATOR LIGHT AND
AUDIBLE ALARM
2 INCH PRIMARY AND SECONDARY AIR
PRESSURE GAUGES
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
PRECO 1040 87 DB TO 112 DB AUTOMATIC
SELF-ADJUSTING BACKUP ALARM
ELECTRONIC CRUISE CONTROL WITH
SWITCHES IN LH SWITCH PANEL
KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE
DISPLAY: 1X7 CHARACTER, 26 WARNING
LAMPS, DATA LINKED, ICU3
DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN,
SAE J1939, LOCATED BELOW DASH
2 INCH ELECTRIC FUEL GAUGE
PROGRAMMABLE RPM CONTROL -
ELECTRONIC ENGINE
ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE
TRANSMISSION OIL TEMPERATURE INDICATOR
LIGHT
ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY
CUSTOMER FURNISHED AND INSTALLED PTO
CONTROLS

Description

NO LANE DEPARTURE WARNING SYSTEM
ELECTRIC ENGINE OIL PRESSURE GAUGE
AM/FM/WB RADIO WITH BLUETOOTH AND
MICROPHONE, FRONT USB PORT, FRONT AND
REAR AUXILIARY INPUTS AND J1939
DASH MOUNTED RADIO
(2) RADIO SPEAKERS IN CAB
AM/FM ANTENNA MOUNTED ON FORWARD LH
ROOF
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
STANDARD VEHICLE SPEED SENSOR
ELECTRONIC 3000 RPM TACHOMETER
IDLE LIMITER, ELECTRONIC ENGINE
TWO ON/OFF ROCKER SWITCHES IN THE DASH
WITH INDICATOR LIGHTS AND WIRE ROUTED
TO CHASSIS AT BACK OF CAB, LABEL OPT
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR
WITH DELAY
MARKER LIGHT SWITCH INTEGRAL WITH
HEADLIGHT SWITCH
ONE VALVE PARKING BRAKE SYSTEM WITH
DASH VALVE CONTROL AUTONEUTRAL AND
WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, WASHER/WIPER AND HAZARD IN
HANDLE
INTEGRAL ELECTRONIC TURN SIGNAL
FLASHER WITH HAZARD LAMPS OVERRIDING
STOP LAMPS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: N0006EA WHITE ELITE SS
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
NO FUEL TANK CABINET PAINT
POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)



Description

BUMPER PAINT: FP24812 ARGENT SILVER
DUPONT FLEX

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY


Extended Warranty

TOWING EXTENDED/ROADSIDE SERVICE WARRANTY, 6
MONTHS/UNLIMITED MILES/KM, \$550 CAP

Dealer Installed Options

| | Weight Front | Weight Rear |
|---|-----------------|----------------|
| BRUSH HOG MODEL G-2224C PER ATTACHED SPEC. | 0 | 0 |
| MANUAL TARP SYSTEM | 0 | 0 |
| Total Dealer Installed Options | 0 lbs | 0 lbs |

EQUIPMENT LIST
CITY OF RIVIERA BEACH
December 9, 2015



Model shown with additional options

New Brush Hawg Model G-2224C Grapple Loader

Planetary Gear Drive

Hot Shift PTO

Direct Mount Pump

Programmed Overspeed Protection

4-Way Stabilizers

Stabilizer LED Strobe Lights

Dual Operator Control Stations: Controls Forward & Level Platform

24" Walk-Thru

Main Boom, Tip Boom and Tip Boom Extension

Hose Retract Box

Rotator

Municipal Bucket: Bolt-On, Reversible Bucket Edges; Adjustable Friction Brake; Bucket

Cylinder Covers

18' Tapered Dump Body (42"-74")

Manual Tarp

3/16" Single Sheet Floor

4" Crossmembers on 12" Centers

12GA Sides

12GA Side Posts on 24" Centers

7GA Rear Posts

Single Rear Door

15 Ton Scissor Hoist, Single Body Prop

Primed and Painted Solid Color

Undercoating on Bottom of Dump Body

City of Riviera Beach Option Package:

Tool Box in Front of Dump Bed

Underbody Tool Box

Underbody Tool Holder

Upper Rear Door Brake Lights

Upper Rear Door Strobe Lights

Mounted Wheel Chocks

Mounted Fire Extinguisher

Boom Over Height Light and Alarm

Stabilizer Not Retracted Light and Alarm

Body Up Light and Alarm

Back Up Camera System



2840 Center Port Circle
Pompano, Bch, FL. 33064



PURCHASER: RIVIERA BEACH

DATE: 12/16/2015

ADDRESS:

PHONE:

CITY: RIVIERA BEACH FL

ATTN: PRINCE ALEXANDER

| | | | |
|-------------|---|--------|-----------|
| BASE MODEL: | SPEC 12 15-13-0904 FLORIDA SHERIFFS CONTRACT FREIGHTLINER | PRICE: | \$40,931 |
| OPTION # | 35-35000GVW 35000 GVW PACKAGE WITH ALLISON 3500RDS | PRICE: | \$28,900 |
| OPTION # | BRUSH HAWG LOADER AND TRASH BODY G-224C | PRICE: | \$69,800 |
| OPTION # | 545-632 C.A. 180 TO 186 FOR BRUSH HAWG | PRICE: | \$990 |
| OPTION # | 727-1AH AIR HORN | PRICE: | \$120 |
| OPTION # | DLR-MF MUD FLAPS | PRICE: | \$290 |
| OPTION # | DLR-BUA BACKUP ALARM | PRICE: | \$190 |
| OPTION # | 452-001 DRIVER CONTROLLED DIFF LOCK REAR AXLE | PRICE: | \$690 |
| OPTION # | 101-2N7 280 HP CUMMINS ENGINE \$10,990 LESS ISL ON PACK 35GVW | PRICE: | \$6,640 |
| OPTION # | THIS INCLUDES ALL ITEMS ON FREIGHTLINER PRINTOUT. | PRICE: | |
| OPTION # | | PRICE: | |
| OPTION # | | PRICE: | |
| OPTION # | | PRICE: | |
| OPTION # | | PRICE: | |
| OPTION # | TOTAL PRICE | PRICE: | \$148,551 |

Budget Challenges?

Daimler Truck Financial offers special municipal financing programs to help fund the purchase of needed vehicles and other equipment.

TOTAL PRICE: \$0.00

***MTHLY PAYMENT: \$0.00**

- Monthly, annual, semi-annual or quarterly payment options
- Flexible repayment terms (tied to your budget)

*Actual rate, terms, down payment, and program eligibility will be determined by DTF credit team based upon credit worthiness and experience of customer.